

TRC 75

FEATURES & BENEFITS

The TRC 75 Tracked Radial Stockpiling Conveyor is capable of stockpiling material from primary/secondary shredders and screens. The mobility and flexibility of the TRC 75 eliminates the double handling of material with wheel loaders onsite. The TRC 75 caters for a range of applications including compost, C&D waste, sand and gravel, topsoil and waste wood.



Fully protected powerunit with easy access for service and maintenance

Tier 3: Stage 3A CAT 4.4 - 4 cylinder diesel engine developing 83kW (111HP) @1800rpm

Tier 4: Tier 4F / Stage IV - Caterpillar C4.4 - 4 cylinder diesel engine developing 82kW (110HP) @ 1800rpm

Fuel tank volume: 180 litres

TRANSPORT DIMENSIONS	TRC 75
Length	15.6m (51' 3")
Width	2.25m (7' 5")
Height	3m (9' 9")
Weight (Est.)	19,500kg (42,990lbs)
Containerised shipping	40' x 9' 6" High Cube Container

CONVEYOR DETAILS	TRC 75
Conveyor length	22.9m (75' 2")
Belt width	1,050mm (42")
Discharge height	9m (29' 6") @ 18°
Max. discharge height	10.9m (35' 9") @ 23°
Production capacity	Up to 600TPH (661 US TPH)**

OPTIONS

- Canvas dust covers on discharge conveyor
- Canvas dust covers complete with dust hood on discharge conveyor
- Full length side skirting along discharge conveyor
- High spec discharge conveyor head drum scraper
- Anti-roll back flaps
- Discharge belt upgraded to 3ply heavy duty belt
- Discharge conveyor underguard option length of mid section
- Dust suppression at discharge conveyor head drum
- Belt weigher option
- Overband magnet at feedboot of discharge conveyor
- Radio remote to start/stop feeder, raise/lower discharge conveyor
- Pull cord E-stop running length of discharge conveyor
- Radio remote to track machine
- Feedboot lined 6mm wearplate
- Manual adjusting jacking legs at tail side of feeder to adjust tail height
- Hopper lined 6mm wearplate
- Hopper flares lined 6mm wearplate
- Mild steel liners bolted into hopper

**Output potential dependent on feed material and settings. August 2018.